



# Adirondack International Speedway

## MOTORSPORTS & ENTERTAINMENT

### 2019 BARE BONES RULES

The rules herein shall refer to Adirondack International Speedway as “AIS”. These rules are intended to create affordable and fair competition. While they offer a good outline, every item cannot be covered by a written rule. Any questions regarding any item not specifically covered in these rules should be addressed with AIS Officials prior to proceeding. No car, component, or equipment will be considered as having been approved by reason of having previously passed through inspection unobserved or undetected. All equipment is subject to inspection and approval by AIS Officials. You may be assessed penalties including, but not limited to: added weight, fines, loss of points, loss of handicapping, and suspension, car parts, components, and/or equipment deemed as not in compliance with these rules. Any car part, component, and/or equipment which does not conform to the specifications or tolerances contained in the 2019 rules book or is not otherwise approved by AIS may not be used in competition in 2019, and is subject to confiscation at the discretion of AIS Officials.

By competing at AIS, you agree to have read the AIS 2019 General Rule book and the 2019 Bare Bones rule book.

#### **ELIGIBLE VEHICLES**

- Any four (4) cylinder naturally aspirated engine (single or dual overhead camshaft) cars allowed.
- Front wheel or rear wheel drive only (no all wheel drive cars allowed).
- All airbags must be removed.
- Must register year, make and model of car with the tech officials.
- No turbo charged, supercharged and or rotary powered cars allowed.
- No sports cars allowed.
- Must retain OBDII plug-in so Tech can use it.
- Must have a tech manual that contains specifications for the vehicle at all times.

#### **BODY**

- Bodies must be OEM to year, make and model of car.
- No self-tapping screws of any kind allowed.
- No sunroofs allowed - must be completely covered over with at least 20 gauge steel.
- No fiberglass roofs of any kind allowed.
- Side skirts and front air dams are NOT permitted.
- All glass and plastic must be removed.

#### **INTERIOR**

- Complete factory floor pan must be used. NO EXCEPTIONS. Must be free from all holes.

#### **WINDSHIELD AND REAR WINDOW GLASS**

- Factory windshield can be used, providing it is free of any and all cracks.
- Wire mesh or Lexan can be used and must have two (2) 1”x1/8” pieces of flat bar welded from center of roof down to dash supporting wire or Lexan.
- 3” maximum visor is allowed.
- NO mirrors allowed.

## **BUMPERS**

- All cars must have stock bumpers.
- NO front air dams will be permitted on front bumpers.
- Safety chains are mandatory front and rear for towing purposes.

## **CHASSIS**

- Stock frames only. Must be straight.
- NO welding, cutting, chopping or lowering of frame will be allowed.

## **ROLLCAGE**

- Minimum required is a hoop behind drivers seat. Must be made out 1 1/2" x .095 wall tubing.
- Must have a 1/4" thick, 5" square plate under each side of hoop. Welded to the pipe and bolted through the floor with a 1/4" plate on the outside.

## **ENGINE**

- No swapping of cylinder heads between dual or single overhead blocks will be allowed.
- Head part number must match block part number for year, make and model.
- Must be completely as it came from the factory. Absolutely **NO** modifications allowed.

## **EXHAUST**

- OEM exhaust **ONLY**.
- Exhaust must exit behind driver with one muffler.
- Muffler can be 2-1/2" maximum diameter in and out.

## **CARBURETOR**

- Stock OEM fueling only. NO EXCEPTIONS.
- OEM injectors only.

## **COOLING SYSTEM**

- Must be OEM. No aftermarket performance additives allowed.
- No antifreeze allowed (may use Water Wetter or NAPA Kool).

## **BATTERY**

- Battery must be mounted in the trunk or under hood and mounted in a marine type box with cover securely fastened to the chassis.

## **POWERTRAIN**

- Transmission must be OEM no swaps allowed.
- Drive shafts and C.V. shafts must be painted white.
- Rear wheel drive cars must have two (2) drive shaft safety hoops.
- Welded transaxles and differentials are allowed.

## **SHOCKS**

- Must be OEM for year, make and model.
- No performance struts allowed.
- No coil overs allowed.

## **SUSPENSION**

- No spring modifications allowed. Rubber spring spacers **ONLY** will be allowed.
- No cutting, welding or heating of springs is allowed.
- No progressive rate springs allowed.
- Camber and Caster must be within OEM specifications. NO adjustments allowed.

## **BRAKES**

- Brakes on all 4 corners must work at all times.
- No shutoffs allowed.
- No brake bias adjusters allowed.

## **STEERING**

- Steering column must be in stock OEM location.
- Quick release steering wheel is recommended.
- Steering shaft and steering wheel center must be padded.
- Steering must be for year ,make and model of car.

## **FIRE EXTINGUISHER**

- Onboard fire extinguisher is mandatory and must be within driver's reach.

## **DRIVER SEAT**

- Aluminum high back race seat mandatory.
- Seat must be mounted with 4-3/8" bolts in seat bottom and 2-3/8" bolts in seat back (must use fender washers on all bolts).
- Right side padded head restraint is recommended.
- NO fiberglass seats allowed.

## **DRIVER RESTRAINT/PADDING**

- 5-point harness free from cuts, tears, frays or holes is mandatory.
- Harness must be five 5 years old or newer and have the SFI tag on them.

## **WINDOW NET**

- Approved SFI rated safety net is mandatory.
- Safety net must be equipped with a quick release.

## **FUEL SYSTEM**

- Stock tanks ONLY.
- Stock tanks must remain under car. Extra straps are highly recommended.
- Fuel shutoff mandatory and must be clearly labeled.
- After market in-line EFI fuel pumps allowed, must deliver fuel at the same pressure as the stock pump.

## **TIRES**

- The only tire sizes allowed are 165 to 235; 50,60,65,70 or 75 series.
- No 55 series tires allowed.
- Minimum tread wear rating is 260 or higher and must be visible. NO EXCEPTIONS.
- No camber cut tires allowed.
- No altering of struts to fit tire size.
- Tread depth is 1/8" minimum. NO EXCEPTIONS.

## **WHEELS**

- OEM steel wheels only. Maximum width 8" with minimum backset or offset of 3".
- NO aluminum wheels allowed.
- No wheel spacers of any kind allowed.
- Same size wheels must be used on each side.
- Must have a 1" lug nut on all wheel studs.
- 13, 14 and 15" wheels only.

**DRIVER ATTIRE**

- Neck collar mandatory. Factory manufactured head and neck restraint recommended.
- One or two piece fire suit designed for competitive motorsports use mandatory. MUST BE free from holes, frays or tears.
- Racing shoes or leather boots mandatory.
- Racing gloves mandatory.
- Full-face helmet mandatory (Snell SA2000 approved or newer, NO EXCEPTIONS). No M rated helmets allowed.

**RADIOS**

- One-way radio is mandatory. Frequency is 454.0000.
- No other form of one-way or two-way communication is allowed.

**PROTEST PROCEDURE**

- See General Rules.