



Adirondack International Speedway

MOTORSPORTS & ENTERTAINMENT

2019 PREMIUM 6 CYLINDER RULES

The rules herein shall refer to Adirondack International Speedway as “AIS”. These rules are intended to create affordable and fair competition. While they offer a good outline, every item cannot be covered by a written rule. Any questions regarding any item not specifically covered in these rules should be addressed with AIS Officials prior to proceeding. No car, component, or equipment will be considered as having been approved by reason of having previously passed through inspection unobserved or undetected. All equipment is subject to inspection and approval by AIS Officials. You may be assessed penalties including, but not limited to: added weight, fines, loss of points, loss of handicapping, and suspension, car parts, components, and/or equipment deemed as not in compliance with these rules. Any car part, component, and/or equipment which does not conform to the specifications or tolerances contained in the 2019 rules book or is not otherwise approved by AIS may not be used in competition in 2019, and is subject to confiscation at the discretion of AIS Officials.

By competing at AIS, you agree to have read the AIS 2019 General Rule book and the 2019 Premium 6 Cylinder rule book.

ELIGIBLE VEHICLES

- Any six (6) cylinder naturally aspirated engine (V6 or Inline 6) cars allowed.
- Front wheel or rear wheel drive only (no all wheel drive cars allowed).
- All airbags must be removed.
- Must register year, make and model of car with the tech officials.
- No turbo charged, supercharged and or rotary powered cars allowed.
- No sports cars, convertibles or SUV's.

BODY

- Bodies must be OEM to year, make and model of car.
- No self-tapping screws of any kind allowed.
- No sunroofs allowed - must be completely covered over with at least 20 gauge steel.
- No fiberglass roofs of any kind allowed.
- Side skirts are NOT permitted.
- No hood scoops allowed
- Cowl needs to be covered to prevent hot fluids or fire entering driver compartment
- All glass and plastic must be removed.

INTERIOR

- Complete factory floor pan must be used. NO EXCEPTIONS. Must be free from all holes.

WINDSHIELD AND REAR WINDOW GLASS

- Factory windshield can be used, providing it is free of any and all cracks.
- Wire mesh or Lexan can be used and must have two (2) 1”x1/8” pieces of flat bar welded from center of roof down to dash supporting wire or Lexan.
- NO mirrors allowed.

BUMPERS

- All cars must have stock appearing bumpers.
- NO front air dams will be permitted on front bumpers.
- Safety chains are mandatory front and rear for towing purposes.

CHASSIS

- Stock frames only. Must be straight.
- NO welding, cutting, chopping or lowering of frame will be allowed.

ROLLCAGE

- 6-point roll cage of 1-1/2"x.095" wall tubing mandatory. Must have suitable headroom for driver.
- No front tubing in engine compartment allowed.
- Must have at least three (3) pipes of 1-1/2"x.095 thickness welded horizontally to the driver side roll cage.
- Must have at least four (4) pipes of 1-1/2"x.095 thickness welded vertically to the driver side roll cage.
- No kinked or torch bent pipes allowed. Must be all mandrel bent. NO EXCEPTIONS.
- Must be free from holes, tears or any bubble gum welds. THIS WILL BE STRICTLY ENFORCED.
- All pipes will be completely welded.
- 1/8" steel plate welded to the entire driver side door bars is mandatory.
- Rear strut bracing is allowed ONLY from strut tower to strut tower.
- Must have four (4) 1/4" thick x 5" square steel plates welded and bolted underneath each main down pipe on rollcage.

GROUND CLEARANCE

- Minimum ride height is 5".

ENGINE

- OEM engine for year, make and model only.
- Head part number must match block part number for year, make and model.
- OEM type pistons only.
- No dome pistons allowed.
- Milling of head allowed to clean gasket surface (with tech approval).
- Decking of block allowed to clean gasket surface (with tech approval).
- When rebuilding engine, if the head or block has been machined, the use of a thicker head gasket is required to maintain stock compression.
- All sensors will be in stock locations.
- Cold air intake allowed (if car has an air temperature sensor, it must be installed in the cold air intake tube). NO EXCEPTIONS.
- No cutting harness to adapt to different style sensors.
- If engine wiring harness is repaired, it must be approved by tech.

EXHAUST

- Stock exhaust manifolds only.
- Exhaust must exit behind driver with one muffler.
- Muffler must be 2-1/2" maximum diameter in and out allowed.

CARBURETOR

- Stock OEM fueling only.
- OEM injectors only.
- Pre 1996 cars will use a Holley 350 cfm 2 bbl carb only (part number #0T7448).
- No HP carbs or metering blocks allowed.

- Maximum spacer is one inch (1”).
- Spacer must be open hole - no tapering or hour glassing of any kind allowed.

COOLING SYSTEM

- Must be OEM. No aftermarket performance additives allowed.
- No antifreeze allowed (may use Water Wetter or NAPA Kool).

BATTERY

- Battery must be mounted in the trunk or under hood and mounted in a marine type box with cover securely fastened to the chassis.
- Master switch is mandatory and must be clearly labeled and within driver's reach and kill all power when turned off, including electric fuel pump.

POWERTRAIN

- Transmission swaps are allowed as long as it is a direct bolt-in replacement for year, make and model.
- No fabricating mounts allowed (IF IT DOESN'T FIT, DON'T USE IT).
- Drive shafts and C.V. shafts must be painted white.
- Rear wheel drive cars must have two (2) drive shaft safety hoops.
- Welded trans-axles and differentials are allowed.

SHOCKS

- Must be OEM for year, make and model.
- No performance struts allowed.
- No coil overs allowed.

SUSPENSION

- No spring modifications allowed. Rubber spring spacers ONLY will be allowed.
- No cutting, welding or heating of springs is allowed.
- No progressive rate springs allowed.
- 5 degrees camber maximum on RF ONLY. You may redrill strut tower to accommodate for adjustment, NO slotting of strut tower or bottom of strut allowed.
- Caster must be within OEM specifications.

BRAKES

- Brakes on all 4 corners must work at all times.
- No shutoffs allowed.
- No brake bias adjusters allowed.

STEERING

- Steering column must be in stock OEM location.
- Quick release steering wheel is recommended.
- Steering shaft and steering wheel center must be padded.
- Steering must be for year ,make and model of car.

FIRE EXTINGUISHER

- On board fire extinguisher is mandatory and must be within driver's reach.

DRIVER SEAT

- Aluminum high back race seat mandatory.
- Seat must be mounted with 4-3/8” bolts in seat bottom and 2-3/8” bolts in seat back (must use fender washers on all bolts).
- Right side padded head restraint highly recommended.
- NO fiberglass seats allowed.

DRIVER RESTRAINT/PADDING

- 5-point harness free from cuts, tears, frays or holes is mandatory.
- Harness must be five 5 years old or newer and have the SFI tag on them. To be eligible for use in the 2019 season, belts must be stamped 2014 or later.
- All pipes within drivers reach will be padded.

WINDOW NET

- Approved SFI rated safety net is mandatory.
- Safety net must be equipped with a quick release.

WEIGHT

- 2600lbs minimum weight
- 55% maximum left side weight.

FUEL SYSTEM

- 12 gallon fuel cell maximum.
- Stock tanks can be used.
- Stock tanks must remain under car. Extra straps are highly recommended.
- Fuel cell installation must be mounted inside trunk in a 20 gauge steel can with two (2) 1"x1/8" steel flat bar straps mounted to chassis.
- If using a fuel cell there must be a firewall free from holes between trunk area and driver area.
- Fuel shutoff mandatory and must be clearly labeled.
- After market in-line EFI fuel pumps allowed, must deliver fuel at the same pressure as the stock pump.

TIRES

- The only tire sizes allowed are 165 to 235; 50,60,65,70 or 75 series.
- No 55 series tires allowed.
- Minimum tread wear rating is 260 or higher and must be visible. NO EXCEPTIONS.
- No camber cut tires allowed.
- No altering of struts to fit tire size.
- Tread depth is 1/8" minimum. NO EXCEPTIONS.

WHEELS

- OEM steel wheels only. Maximum width 8" with minimum backset or offset of 3".
- NO aluminum wheels allowed.
- Bassett or Aero standard weight wheels allowed. No lightweight wheels permitted.
- No wheel spacers of any kind allowed.
- Same size wheels must be used on each side.
- Must have a 1" lug nut on all wheel studs.
- 13, 14 and 15" wheels only.

DRIVER ATTIRE

- Neck collar mandatory. Factory manufactured head and neck restraint recommended.
- One or two piece fire suit designed for competitive motorsports use mandatory. MUST BE free from holes, frays or tears.
- Racing shoes or full leather boots mandatory.
- Racing gloves mandatory.
- Full-face helmet mandatory (Snell SA2000 approved or newer, NO EXCEPTIONS). No M rated helmets allowed.

RADIOS

- One-way radio is mandatory. Frequency is 454.0000.
- No other form of one-way or two-way communication is allowed.

PROTEST PROCEDURE

- See General Rules.